

## ELAPRO Top 1k-SIL

TD312 Processing instructions

### Kurzanleitung

- Cleaning the substrate
- Apply ELAPRO Top 1k-SIL single layer to the dried ELAPRO synthetic liquid sealant (for example Balkondicht 1k-CRYL)

### ► Direct to the processing video with QR code - that's how it works



*iPhone:* Open the camera app and point to the QR code. *Android-Phone:* In web browser open webqr.com, click on video camera icon and point to the QR code. Alternatively, download an appropriate app

### Surface preparation

If the base sealant has been applied for some time prior to Top 1k-SIL, it must be ensured that the substrate is free of dust, oil and grease for processing. Deposits, mosses and lichens are to be removed without residue.

In order to ensure a consistently homogeneous surface structure, the surface of the ELAPRO Balkondicht 1k-CRYL should be lightly sanded after hardening.

### Sealing base sealant

For the sealing of balcony and terrace surfaces with ELAPRO Balkondicht 1k-CRYL see TD212 Processing Instructions.

### Sealing with Top 1k-SIL

ELAPRO Top 1k-SIL must be stirred thoroughly and slowly. Avoid rapid stirring to prevent air from entering the material. The processing takes place with a roll.

#### Primer

For the sealing of surfaces made of ELAPRO Balkondicht 1k-CRYL no primer is required. For the sealing of surfaces based on other materials, please contact our customer service.

#### Topcoat

0.30 kg of ELAPRO Top 1k-SIL are applied to the substrate as a single layer per square meter. The material must be distributed evenly over the entire surface in order to build up a uniform layer thickness.

### Storage & Durability

In original packaging, stored cool, dry, frost-free and airtight, at least 6 months shelf life. Keep container in a well-ventilated place. Direct solar radiation must also be avoided on the construction site. Opened containers of Top 1k-SIL should be processed promptly

### Consumption

Min. 0.30 kg/m<sup>2</sup>

### Disposal

Liquid: EAK 08 04 10

Emptied: EAK 08 04 10

### General remarks

Please also note the following documents:

- TD312 Processing instructions
- TD314 Safety data sheet

### Processing information

An assessment of the proper subsurface texture is, according to VOB, the responsibility of the processor. He has to convince himself before the beginning of the sealing work on the coating-fair condition of the substrate.

### Hazard warnings

Non

### Compatible system components

- ELAPRO Balkondicht 1k-CRYL
- ELAPRO Dachdicht 1k-CRYL
- ELAPRO Dachdicht 1k-SIL

### General information

All data provided herein are for the purpose of describing the material only and are based on tests and results obtained from practical use. Therefore no guarantee can be given for their accuracy or completeness. Consultations are made to the best of our knowledge. Color deviations or changes have no influence on the technical parameters of the products. Times are shortened at higher and extend at lower ambient and surface temperatures. All data are subject to change without notice. The data sheet loses its validity no later than 5 years after its publication. The information and recommendations contained in this product information correspond to the current state of our knowledge and serve to inform the buyer. They do not release the buyer to check the products for their suitability and use on the respective surface. The products described may only be processed in the system with the system components

mentioned here. We guarantee perfect quality within the scope of our terms of delivery and payment.

### **Safety instructions**

---

All safety regulations on the containers, the technical product information and the safety data sheets as well as the relevant local, national and EU regulations must be observed. Care must be taken for personal safety at work.